## **Nexus**® **1252**For Easy Viewing of Voltage, Current and Power

## 19-inch Rack Mount

Meter Assembly



- Ideal for Substation 19" Rack
  Mount Control Panel Applications
- Incorporates Nine Simultaneous Lines of Display
- Provides Clear and Easy Viewing of Data with No Scrolling
- Built-in Testing Switch
- Designed Specifically for Nexus® 1252 Meters
- Front Panel Download Port

Electro Industries/GaugeTech introduces a new rack assembly that offers the Nexus® 1252 advanced performance power meter and power quality recorder together with nine LED lines of display in one mountable unit.

The 19" rack assembly also features a built-in test switch and a front download port. These displays allow for 3 phases of voltage, 3 phases of amps, Watt/VAR, and PF displayed simultaneously with no need to scroll.


The three LED displays consist of the following:

- P40N+: Master LED display providing either multifunction measurement or use as a Volts 3 line master unit.
- P41N+: LED Amps display Slave 3 line display
- P43N+: LED Power display Slave 3 line display



## Wiring

The displays are connected to the meter through their back serial ports. The serial port connection from the displays is connected to Port 3 of the Nexus® 1252 meter. There is a serial port connection from Port 1 of the Nexus® 1252 meter to the front of the mounting unit.



ption	Model	Memory	Input Voltage	Control Power	Nominal Frequency	V-Switch™ Pack	Internal Expansion Port Options	Revenue Seal	Style Option
umbers:									
Example:	1252	A	120	D	60	V1	Х	Х	4RU3DS
	1252	<b>A</b> Advanced	<b>120</b> 0-150 Volts PH-N 0-300 Volts PH-PH	D 18-60V DC Power Supply	<b>60</b> Hz	<b>V1</b> Standard Nexus® 1252 Meter	<b>X</b> No Expansion Port	<b>X</b> (No Seal)	<b>4RU3DS</b> 3 Display
			<b>G</b> 300 Volts PH-N 600 Volts PH-PH	<b>D2</b> 90-276 Volts AC/DC Power Supply	<b>50</b> Hz	<b>V2</b> Advanced	INP2 56k with Dial-Out	ICR Revenue Seal	
					<b>400</b> Hz		<b>INP200</b> 10/100BaseT Rapid Response™ Ethernet		

## Accessory Options

WEIGHT **DIMENSIONS BOX PACKAGING DIMENSIONS** 16 lbs (with packaging) 24 inches (60.96 cm) LENGTH 19 inches (48.26 cm) LENGTH HEIGHT 7 inches (17.78 cm) HEIGHT 18 inches (45.72 cm) DEPTH 14 inches (35.56 cm) DEPTH 18 inches (45.72 cm)

