

# Current Transformer

## Model EI-5SP-1200-00

Window Size 2.88" x 4.25"



Catalog Number	Current Ratio	Accuracy @ 60 Hz *		Nominal Winding Resistance (ohm)	Lead Wire Size (AWG)
		±%	Burden (VA)		
EI-5SP-1200-00	1200:5A	1.0	10	0.40	16

## Specifications

- Secondary sources 5 A AC at rated F.S. primary current.
- Nominal operating frequency range is (50 - 400) Hz.
- Thermal rating factor is 1.33 @ 30 °C for all ratios.
- Insulation voltage class is 0.6 kV BIL 10 kV.
- For indoor applications only.
- Lead wire length is 36 inches.
- CT can be split apart and reassembled onto the primary conductor without interrupting service.


### NOTE: Safety precautions must be observed.

- CT is finished in heavy vinyl tape with dipped acrylic overcoat; uses embedded SS band to secure two halves of transformer together.

### Notes for diagram on the right:

- Dimensions are in inches.
- All dimensions are for reference only.
- All dimensions are measured over the highest point of the appropriate surface.
- White lead wire is electrically in phase with "HI" side of transformer (with polarity marks).

**CAUTION!** Potentially lethal voltages may appear on terminals if the terminals are not electrically connected together when installing onto an energized system. It is imperative that leads and/or terminals be shorted together or attached to the intended burden prior to such installation.



1800 Shames Drive  
Westbury, NY, 11590

1-877-EIMETER  
(1-877-346-3837)

Tel: 516-334-0870  
Fax: 516-338-4741

Email: [EIG\\_sales@hubbell.com](mailto:EIG_sales@hubbell.com)  
Website: [www.electroind.com](http://www.electroind.com)

