

FREQUENCY:

60 Hz

**STANDARD
SECONDARY VOLTAGE:**

120 Volts

INSULATION LEVEL:

600 Volt, 10 kV BIL full wave

ACCURACY CLASS: (Per Phase)

0.6 W, 1.2 X

THERMAL RATING: (Per Phase)

150 VA at 30°C amb., 100 VA at 55°C amb.

Terminals are brass screws No. 8-32
with one lockwasher and flatwasher.

Approximate weight is 15.5 lbs.




Clear Plastic Cover

CATALOG NUMBER	VOLTAGE RATING	URNS RATIO	REC. PRIMARY FUSE RATING
EI-2VT460-480FF	480:120	4:1	1.0

Model EI-2VT460-480FF

- The core and coil assembly are encased in a thermoplastic shell and filled with resin.
- These transformers are designed for open delta connection.
- Primary fuses are type CC rejection style.
- It is desirable to use a 1.6 Amp BBS type or equal fuse in the secondary, to protect the transformer.
- Models designed specifically for 50Hz operation are available with reduced performance. Consult factory for details.
- This page contains a circle diagram for the estimation of the errors or other-than-rated burdens.



CONNECTION DIAGRAM

VOLTAGE TRANSFORMER CIRCLE DIAGRAM
THIS GRAPH IS DRAWN FOR A 60Hz 0.6 P.F. SYSTEM LOAD

