

# B10U

## Zero-Power ANSI Optical Probe

Communication for ANSI Socket Meters



### Features

- Requires No Power Supply
- Baud Rate - up to 38400 bps
- ANSI Type 2 Compatible
- Works Great with Shark® 270 and Nexus® Series Socket Revenue Meters
- Includes 2 Meter Cable
- Bidirectional Interface
- Strong Magnetic Adhesion that Complies with IEC 62056-21/ANSI C12.18
- USB 2.0 Standard Connector

### Description

The B10U is a zero power optical communication probe. Its bidirectional interface utilizes infrared light. It provides an ANSI-rated optical communication interface for programming and reading EIG's Shark® 270 and Nexus® series socket revenue meters through their optical port.

### Specifications

- **Standards:** IEC 62056 standard, ANSI C12.18 and ANSI C12.18 type two-2007 standard
- **Interface:** Infrared optical
- **Connector:** USB 2.0
- **Baud Rate:** Up to 38400 bps
- **Compatible with:** Windows 2000/XP/Vista/7/8/10
- **Cable:** 2 meter (6.5 feet) straight cable.
- **Temperature:** - 15 °C ~ 80 °C (5 °F - 176 °F)

### Ordering Information

**Order Number:** B10U



1800 Shames Drive, Westbury, NY 11590 **1-877-EIMETER**  
(1-877-346-3837) **Tel:** 516-334-0870 **Fax:** 516-338-4741  
**Email:** sales@electroind.com **www.electroind.com**



**B10U web page:**

E128772 021621 V.1.01