

P70N Color Touchscreen Display

FOR THE NEXUS[®] 1450 CYBER SECURE POWER QUALITY METER



Description

The P70N color touchscreen display is designed for use with EIG's Nexus[®] 1450 cyber secure power quality meter. It enables remote monitoring of energy and power quality data. The P70N can display data from up to four connected Nexus[®] 1450 meters. It comes standard with a 6 foot power supply cable and has an optional ANSI mounting kit. The P70N easily connects via one of the Nexus[®] 1450 meter's four RS485 ports. Refer to the Nexus[®] 1450 Meter User Manual for wiring and mounting instructions.

Features

- View meter readings remotely.
- 50+ pre-configured display screens.
- Meter readings and power quality data.
- Multiple meter support.
- Easy setup.



Specifications

Maximum Input Voltage	24 V DC
Minimum Input Voltage	12 V DC
Power Consumption	3.6 W or less
Operating Temperature Range	(0 to 50) °C / (32 to 122) °F
Storage Temperature Range	(-20 to 60) °C / (-4 to 140) °F
Protection Class	IP65, Indoor Use Only
Overall Dimensions (H x W)	(3.05 x 4.59) inches / (7.75 x 11.65) cm
Display Screen	4.3 inches (10.92 cm) color display with a resistive touch screen overlay

Ordering Information

Part Number	P70N
ANSI Mounting Kit	SMKP70N

1800 Shames Drive
Westbury, NY, 11590

Tel: 1-877-EIMETER
(1-877-346-3837)

Email: EIG_sales@hubbell.com
Website: www.electroind.com

